





## M18 BDD-O | M18™ compact drill driver



- Compact drill driver measuring only 185 mm in length, making it ideal for working in confined spaces.
- Milwaukee®'s high performance 4-pole motor delivers maximum power whilst maximising the power to weight ratio.
- REDLINK™ overload protection electronics in tool and battery pack deliver best in class system durability.
- Full metal gear box delivers maximum performance and long life.
- 13 mm metal chuck for quick bit changes and bit retention.
- 17 stage torque adjustment plus additional drilling for maximum flexibility.
- Individual battery cell monitoring optimises tool run time and ensures long term pack durability.

## M18 BDD-O | M18™ compact drill driver



- Compact drill driver measuring only 185 mm in length, making it ideal for working in confined spaces.
- Milwaukee®'s high performance 4-pole motor delivers maximum power whilst maximising the power to weight ratio.
- REDLINK™ overload protection electronics in tool and battery pack deliver best in class system durability.
- Full metal gear box delivers maximum performance and long life.
- 13 mm metal chuck for quick bit changes and bit retention.
- 17 stage torque adjustment plus additional drilling for maximum flexibility.
- Individual battery cell monitoring optimises tool run time and ensures long term pack durability.

	M18 BDD-0
Sound pressure level (dB(A))	84.7
Sound pressure level uncertainty (dB(A))	3
Sound power level (dB(A))	95.7
Sound power level uncertainty (dB(A))	3
Vibration screw driving (m/s <sup>2</sup> )	0.66
Vibration screw driving uncertainty (m/s <sup>2</sup> )	1.5
Vibration drilling into Metal [m/s <sup>2</sup> ]	0.95
Vibration drilling into metal uncertainty [m/s <sup>2</sup> ]	1.5
Vibration drilling into concrete [m/s <sup>2</sup> ]	13
Vibration drilling into concrete uncertainty [m/s <sup>2</sup> ]	1.5
No load speed gear 1 (rpm)	0 - 450
No load speed gear 2 (rpm)	0 - 1800
Max. torque (Nm)	50
Voltage (V)	18
Battery pack capacity (Ah)	-
Battery type	Li-ion
Supplied in	-
Charger supplied	-
No. of batteries supplied	0
Wood screws to (mm)	7
Standard equipment	Bit holder, belt hook, bit
Weight with battery pack (kg)	-
Max. drilling steel (mm)	13
Max. drilling wood (mm)	38
Chuck capacity (mm)	13

	M18 BDD-0
Sound pressure level (dB(A))	84.7
Sound pressure level uncertainty (dB(A))	3
Sound power level (dB(A))	95.7
Sound power level uncertainty (dB(A))	3
Vibration screw driving (m/s <sup>2</sup> )	0.66
Vibration screw driving uncertainty (m/s <sup>2</sup> )	1.5
Vibration drilling into Metal [m/s <sup>2</sup> ]	0.95
Vibration drilling into metal uncertainty [m/s <sup>2</sup> ]	1.5
Vibration drilling into concrete [m/s <sup>2</sup> ]	13
Vibration drilling into concrete uncertainty [m/s <sup>2</sup> ]	1.5
No load speed gear 1 (rpm)	0 - 450
No load speed gear 2 (rpm)	0 - 1800
Max. torque (Nm)	50
Voltage (V)	18
Battery pack capacity (Ah)	-
Battery type	Li-ion
Supplied in	-
Charger supplied	-
No. of batteries supplied	0
Wood screws to (mm)	7
Standard equipment	Bit holder, belt hook, bit
Weight with battery pack (kg)	-
Max. drilling steel (mm)	13
Max. drilling wood (mm)	38
Chuck capacity (mm)	13

